

Key Type Drill Chucks

TYPE: G



- Representative products, super precision durable & rigity
- Big outside diameter suit for heavy duty
- The nut and jaws adopt AISI-52100 (bearing steel) and heat-treated, durability the precision can be Issted.
- The taper is precision ground, advance the precision.
- Accuracy: 90mm length within 0.08mm
- With keys



ORDER NO.	TYPE	Clamping Capacity		Female Taper DIN or Jacobs	OUTER Ø / mm	Length		Wt g	Key Size	QTY Pcs./ Cu-Ft	N.W/G.W kgs	CODE NO.
		mm	inch			Open B mm	Closed A mm					
10006	G-6H	0.5-6.5	1/64"-1/4"	J1	32	41	50	200	CK3	100/0.82	20/21	3303-001
10018	G-10XH	0.5-10	1/64"-3/8"	J2S	41.5	50.5	64	390	CK4	60/0.85	24/25	3303-004
10050	G-13XH	0.5-13	1/64"-1/2"	J6	56	70.5	88	800	P6	36/0.83	30/31	3303-006
10051				B16	56	70.5	88	800	P6	36/0.83	30/31	3303-007
10052				J33	56	70.5	88	800	P6	36/0.83	30/31	3303-008
10068	G-16XH	1-16	1/32"-5/8"	J3	65	81	101	1000	P7	24/0.84	24/25	3303-009
10070				B18	65	81	101	1000	P7	24/0.84	24/25	3303-010
10074	G-19XH	3-19	1/8"-3/4"	J4	74	99.5	126	2150	P7	18/0.83	39/40	3303-011

Ball Bearing Key Type Super Chucks

TYPE: H



- Suitable for heavy duty drilling use.
- By using anti-thrust bearing to increase the gripping power so that high speed drilling can be performed.
- All parts hardened by heat treatment and precision ground precision can be lasted, super clamping power.
- Accuracy:100m/m length is within 0.08m/m
- With keys

ORDER NO.	TYPE	Clamping Capacity		Female Taper DIN or Jacobs	OUTER Ø / mm	Length		Wt g	Key Size	CODE NO.
		mm	inch			Open B mm	Closed A mm			
12011	10BXH	1-10	1/32"-3/8"	J2S	45	56	64	390	P4	3303-030
12006	13BXH	1-13	1/32"-1/2"	J3	62	75	95	1200	P6	3303-031
12001				J6						3303-032
12002				J33						3303-033
12003	16BXH	1-16	1/32"-5/8"	J3	65	81	101	1500	P7	3303-034
12005	19BXH	1-19	1/32"-3/4"	J4	74	100	130	2150	P7	3303-036